



# Safety Data Sheet

Issue Date 26-Oct-2016

Revision Date 26-Oct-2016

Revision Number 13

## 1. IDENTIFICATION

### Product identifier

**Product Code** N-69-00WHA  
**Product Name** HB EPOXOLINEII TNEMEC WHITE

### Other means of identification

**Common Name** SERIES N69/V69, PART A  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372 816-474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203,  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
 Causes skin irritation  
 Causes serious eye damage  
 May cause an allergic skin reaction  
 Suspected of causing cancer  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Causes damage to organs through prolonged or repeated exposure  
 Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**Other information**

Harmful to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

8.93713 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	10 - 30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - 30%
XYLENE	1330-20-7	1 - 10%
MODIFIED CYCLOALIPHATIC POLYAMINE	68953-36-6	1 - 10%
BENZYL ALCOHOL	100-51-6	1 - 10%
N-BUTANOL (SKIN)	71-36-3	1 - 10%
ETHYL BENZENE	100-41-4	1 - 10%
ISOPHORONE DIAMINE	2855-13-2	1 - 10%
AMORPHOUS SILICA	7631-86-9	1 - 10%
TETRAETHYLENEPENTAMINE	112-57-2	0.1 - 1%
P-P'-ISOPROPYLIDENEDIPHENOL	80-05-7	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Consult a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products**Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Bases. Cleaning solutions such as Chromerge and Aqua Regia.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
-----------	-----------	----------	------------

BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1400 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

**Appropriate engineering controls**

**Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eyeface protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	

pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	116 °C / 241.0 °F	
Flash point	26 °C / 78.0 °F	
Evaporation rate		Pensky Martens - Closed Cup
Flammability (solid, gas)		No data available
Flammability Limit in Air		No information available
Upper flammability limit	12.3	No data available
Lower flammability limit	1.5	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.82981	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	1100 centipoises	approx

**Other Information**

Density	15.26062 lbs/gal
Volatile organic compounds (VOC) content	2.62788 lbs/gal
Total volatiles weight percent	17.22 %
Total volatiles volume percent	36.7 %

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Epoxy constituents.

**Incompatible materials**

Strong oxidizing agents, Acids, Bases, Cleaning solutions such as Chromerge and Aqua Regia

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Aldehydes. Hydrocarbons. Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Vapors may irritate throat and respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )		
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 29.08 mg/L ( Rat ) 4 h
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
ISOPHORONE DIAMINE 2855-13-2	= 1030 mg/kg ( Rat )		
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
TETRAETHYLENEPENTAMINE 112-57-2	= 3990 mg/kg ( Rat )	= 660 µL/kg ( Rabbit )	
P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7	= 3300 mg/kg ( Rat )	= 3 mL/kg ( Rabbit )	> 0.17 mg/L ( Rat ) 6 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5 g/kg ( Rat )	= 14100 µL/kg ( Rabbit )	

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Skin sensitizer. Substances known to be mutagenic to man. Substances known to impair fertility. May cause cancer. Avoid repeated exposure.

**Sensitization** May cause sensitization of susceptible persons.

**Mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3		
XYLENE 1330-20-7		Group 3		
ETHYL BENZENE 100-41-4	A3	Group 2B		X
AMORPHOUS SILICA 7631-86-9		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

**Reproductive effects** Suspected of damaging fertility or the unborn child.  
**STOT - single exposure** Eyes, Central Nervous System (CNS), Skin  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, kidney, liver, Lungs, respiratory system, Skin.

**Aspiration hazard** No information available.

**Acute Toxicity** 8.93713 % of the mixture consists of ingredient(s) of unknown toxicity.  
**The following values are calculated based on chapter 3.1 of the GHS document .**

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

11.87839 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
N-BUTANOL (SKIN) 71-36-3	500: 72 h Desmodosmus subspicatus mg/L EC50 500: 96 h Desmodosmus subspicatus mg/L EC50	100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	1983: 48 h Daphnia magna mg/L EC50 1897 - 2072: 48 h Daphnia magna mg/L EC50 Static
ETHYL BENZENE 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
ISOPHORONE DIAMINE 2855-13-2	37: 72 h Desmodosmus subspicatus mg/L EC50	110: 96 h Leuciscus idus mg/L LC50 semi-static	42: 24 h Daphnia magna mg/L EC50 14.6 - 21.5: 48 h Daphnia magna mg/L EC50 semi-static
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
TETRAETHYLENEMPENTAMINE 112-57-2	2.1: 72 h Pseudokirchneriella subcapitata mg/L EC50	420: 96 h Poecilia reticulata mg/L LC50 static	24.1: 48 h Daphnia magna mg/L EC50
P-P-ISOPROPYLIDENEDIPHENOL 80-05-7	2.5: 96 h Pseudokirchneriella subcapitata mg/L EC50	3.6 - 5.4: 96 h Pimephales promelas mg/L LC50 flow-through 4.0 - 5.5: 96 h Pimephales promelas mg/L LC50 static 4: 96 h Oncorhynchus mykiss mg/L LC50 9.9: 96 h Brachydanio rerio mg/L LC50 static	9.2 - 11.4: 48 h Daphnia magna mg/L EC50 Static 3.9: 48 h Daphnia magna mg/L EC50 10.2: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
-----------	---------

XYLENE 1330-20-7	2.77
BENZYL ALCOHOL 100-51-6	1.1
N-BUTANOL (SKIN) 71-36-3	0.785
ETHYL BENZENE 100-41-4	3.118
ISOPHORONE DIAMINE 2855-13-2	0.79
TETRAETHYLENEPENTAMINE 112-57-2	.99
P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7	2.2
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no.** 1263  
**Proper Shipping Name** paint  
**Hazard Class** 3  
**Packing Group** III  
**Emergency Response Guide Number** 128

**IATA**

**Additional information** Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDL</b>	Complies
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Component</b>	<b>HAPS Data</b>
XYLENE	
ETHYL BENZENE	
BENZENE, 1,3-DIMETHYL	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYL BENZENE - 100-41-4	0.1
P-P'-ISOPROPYLIDENEDIPHENOL - 80-05-7	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3				X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
P-P'-ISOPROPYLIDENEDIPHENOL - 80-05-7	Female Reproductive

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
XYLENE 1330-20-7	X	X	X
BENZYL ALCOHOL 100-51-6		X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
ISOPHORONE DIAMINE 2855-13-2	X		
AMORPHOUS SILICA 7631-86-9	X	X	X
TETRAETHYLENEPENTAMINE 112-57-2	X	X	X
P-P'-ISOPROPYLIDENEDIPHENOL L 80-05-7	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

**16. OTHER INFORMATION**

**NFPA**  
**HMS (Hazardous**  
**Material Information**  
**System)**

Health 2  
Health 2\*

Flammability 3  
Flammability 3

Instability 1  
Reactivity 1

Physical hazard \*

**Prepared By**  
**Revision Date**  
**Revision Summary**  
9 4 5 7 10 8 2 11 14 1

Tnemec Regulatory Dept: 816-474-3400  
26-Oct-2016

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 07-Aug-2015

Revision Date 07-Aug-2015

Revision Number 10

## 1. IDENTIFICATION

### Product identifier

Product Code N-69-0069B  
Product Name H-B EPOXOLINE II CONVERTER

### Other means of identification

Common Name SERIES N69/N69F, PART B  
UN/ID no. 1263

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)  
Emergency Telephone United States: 800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

Danger

**Hazard statements**

Causes skin irritation  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause genetic defects  
 May cause cancer  
 May damage fertility or the unborn child  
 May cause damage to organs through prolonged or repeated exposure  
 Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity

26.1844305 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - 60%
EPOXY RESIN (LER)	25085-99-8	10 - 30%
SOLID EPOXY RESIN	-	10 - 30%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	1 - 10%
XYLENE	1330-20-7	1 - 10%
METHYL ISOBUTYL KETONE	108-10-1	1 - 10%
AROMATIC HYDROCARBON MIXTURE	64742-95-6	1 - 10%
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - 10%
ETHYL BENZENE	100-41-4	1 - 10%
BENZENE, 1,4-DIMETHYL	106-42-3	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Acids. Bases. Amines. Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup> TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	500 ppm

ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
BENZENE, 1,4-DIMETHYL 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

**Appropriate engineering controls**

**Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	98 °C / 208.0 °F		
<b>Flash point</b>	35 °C / 95.0 °F	Pensky Martens - Closed Cup	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>		No information available	
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	N/A		
<b>Lower flammability limit</b>	N/A		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	1.46987	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>	centipoises	approx	

**Other Information**

Density 12.25872 lbs/gal  
 Volatile organic compounds (VOC) content 0.28741 lbs/gal  
 Total volatiles weight percent 17.56 %  
 Total volatiles volume percent 29.86 %

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Acids, Bases, Amines, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Chlorine. Fluorine.

**11. TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

**Inhalation** HARMFUL BY INHALATION.  
**Eye contact** Causes serious eye irritation.  
**Skin contact** Irritating to skin. May cause sensitization by skin contact.  
**Ingestion** Harmful if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
AROMATIC HYDROCARBON MIXTURE 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m³ ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
BENZENE, 1,4-DIMETHYL 106-42-3	= 4029 mg/kg ( Rat )		= 4740 ppm ( Rat ) 4 h = 4550 ppm ( Rat ) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg ( Rat )	= 14100 µL/kg ( Rabbit )	

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** May cause genetic defects.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
XYLENE 1330-20-7		Group 3		
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B		X
ETHYL BENZENE 100-41-4	A3	Group 2B		X
BENZENE, 1,4-DIMETHYL 106-42-3		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

**Reproductive effects** Suspected of damaging fertility or the unborn child.  
**STOT - single exposure** No information available  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Central nervous system, Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin.  
**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 26.1844305 % of the mixture consists of ingredient(s) of unknown toxicity.  
**The following values are calculated based on chapter 3.1 of the GHS document .**

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

18.01842 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
AROMATIC HYDROCARBON MIXTURE 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50

ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
BENZENE, 1,4-DIMETHYL 106-42-3	3.2: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 105.1: 3 h Chlorella vulgaris mg/L EC50	2.6: 96 h Oncorhynchus mykiss mg/L LC50 8.8: 96 h Poecilia reticulata mg/L LC50 semi-static 7.2 - 9.9: 96 h Pimephales promelas mg/L LC50 static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 static	3.55 - 6.31: 48 h Daphnia magna mg/L EC50 Static
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
XYLENE 1330-20-7	2.77
METHYL ISOBUTYL KETONE 108-10-1	1.19
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
ETHYL BENZENE 100-41-4	3.118
BENZENE, 1,4-DIMETHYL 106-42-3	3.15
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
BARIUM SULFATE (TOTAL DUST) 7727-43-7	Toxic
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no.** 1263  
**Hazard Class** 3  
**Packing Group** III  
**Emergency Response Guide Number** 1285

**IATA**

**UN/ID no.** 1263  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDL** Complies  
**EINECS/ELINCS** Does not comply  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

Component	HAPS Data
XYLENE	
METHYL ISOBUTYL KETONE	
ETHYL BENZENE	
BENZENE, 1,4-DIMETHYL	
BENZENE, 1,3-DIMETHYL	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
METHYL ISOBUTYL KETONE - 108-10-1	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,4-DIMETHYL - 106-42-3	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3				X
BENZENE, 1,3-DIMETHYL 108-38-3				X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,4-DIMETHYL 106-42-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
ETHYL BENZENE - 100-41-4	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X

XYLENE 1330-20-7	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard \*  
**HMS (Hazardous** Health 2\* Flammability 3 Reactivity 1  
**Material Information**  
**System)**

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 07-Aug-2015  
**Revision Summary**  
 9 4 5 7 10 8 11 14

**Disclaimer**  
 For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**